

Flow Test Accessories



#501 Inspector's Hydrant Flow Nozzle:

(a.k.a. hydrant flow nozzle, FM nozzle or stream straightener) Designed by New England Manufacturing over 40 years ago. The uninterrupted and straight flow of water through this 6" calibrated flow nozzle compensates for the varied configurations on the inside diameter of the hydrant butt openings. Thus, the operator does not have to know or take into calculation the coefficient of the particular hydrant being flowed. The result is a simpler process with a **more accurate reading**. This all-brass nozzle is nickel plated and has a 2¼" smooth bore ID tube delivering a constant .88 coefficient of flow between 10-56psi. A waterproof decal showing the actual GPM of flow between 10-56psi is affixed to the tube. Available in standard 2½" NST or Canadian 5 TPI.

\$125.00

#502 Brass Flow Nozzle Elbow:

Intended to be used with our Inspector's Hydrant Flow Nozzle, this brass elbow is designed to direct the flow 45 degrees. It can be rotated to any desired position and is available in standard NST threading.

\$125.00



#506 Brass Hydrant Adapter:

A number of areas in the U.S. and Canada do not use NST threading on hydrants. In those cases an adapter is necessary to convert to the standard NST threads. We stock a number of popular adapters.

Average Cost: \$65.00



#503 30" Underwriter's Playpipe:

This is the standard UL and FM approved 30" playpipe. Made with 2½" base and 30" long. Screw nozzle, swivel handle, and Marlin wound red painted cording. Standard discharge tip 1 1/8". Removal of the tip allows for a 1 3/4" flow opening. Stocked in standard NST and Canadian (Ontario) threading.

\$469.95



#301 Brass Hydrant Test Cap: Machined from a brass casting, this rugged 2½" cap is supplied with either US standard NST threads or Canadian Ontario 5TPI. The cap center is machined for ¼" NPT bleeder or gauge connection.

\$49.95